

(19)



JAPANESE PATENT OFFICE

PATENT ABSTRACTS OF JAPAN

(11) Publication number: **11315652 A**

(43) Date of publication of application: **16.11.99**

(51) Int. Cl.

E05B 19/10

E05B 19/04

(21) Application number: **10137797**

(71) Applicant: **CLOVER:KK**

(22) Date of filing: **30.04.98**

(72) Inventor: **NAKAI HATSUO**

(54) **KEY**

COPYRIGHT: (C)1999,JPO

(57) Abstract:

PROBLEM TO BE SOLVED: To provide a key capable of disposing a key plate only by leaving a tongue plate even when improper cutting occurs.

SOLUTION: A tongue plate 2 is mounted on a base end part 10 of a key plate 1 and is held by a coming off prevention member 3. The tongue plate 2 is provided with a key plate insertion hole 22 in which the base end part 10 of the key plate 1 can be inserted or removed and a pair of lock holes 24, 24 which cross this key plate insertion hole 22 orthogonally and pass through in the direction of thickness. In the coming off prevention member 3, a barrel part 30 supported on a surface on one side of the tongue plate 2 and a pair of leg parts 31, 31 inserted into each lock hole 24 are integrally formed. A pawl part 32 locked on a surface on the other side of the tongue plate 2 is formed at a tip of each leg part 31. A cutout part 11 with which each leg part 31 of the coming off prevention member 3 inserted into each lock hole 24 of the tongue plate 2 is formed in the base end part 10 of the key plate 1.

